



MATERIAL SAFETY DATA SHEET

SECTION 1 – GENERAL INFORMATION

Manufacturer:

Modern Masters, Inc.
9380 San Fernando Road,
Sun Valley, California 91352
818-683-0201

HMIS Rating

| | |
|--------------|---|
| HEALTH | 1 |
| FLAMMABILITY | 0 |
| REACTIVITY | 0 |

Emergency Telephone: 800-942-3166**Preparation Date:** May 16, 2005**Revision Date:** March 6, 2007**Product Name:** Wildfire Protective Sealer Matte Acrylic Clear Coat**Product Codes:** WF998

Wildfire® and its symbol are registered trademarks of Wildfire Lighting & Visual Effects, Torrance, CA

SECTION 2 – HAZARDOUS INGREDIENTS

| <u>Hazardous Component</u> | <u>CAS #</u> | <u>OSHA PEL</u> | <u>ACGIH TLV</u> |
|---------------------------------|--------------|-----------------|------------------|
| Diethylene glycol n-butyl ether | 000112-34-5 | N/A | N/A |
| Amorphous silica | 112926-00-8 | 20 ppm | 10 ppm |

SECTION 3 – HAZARD IDENTIFICATION

Emergency Overview: This material is a clear matte acrylic topcoat. It is a stable, non-flammable, clear flowable liquid with a flash point above 200°F.

Primary Routes of Exposure:

Inhalation Skin contact Eye contact

Potential Acute Health Effects:

Inhalation: May cause respiratory tract irritation
Skin: Prolonged or repeated skin contact may cause irritation
Eye: May cause eye irritation
Ingestion: Not hazardous under intended use conditions



MATERIAL SAFETY DATA SHEET

Potential Chronic Health Effects: None known



MATERIAL SAFETY DATA SHEET

SECTION 4 – FIRST AID MEASURES

Eye contact: Flush eyes with clean water for 15 minutes. Seek medical attention.

Skin contact: Thoroughly wash with soap and water before the coating dries.

Inhalation: If irritation occurs, remove to fresh air and seek medical attention if cough or other symptoms develop.

Ingestion: Do not induce vomiting. Seek medical attention.

Note to Physician: Treat symptomatically. This material is basically non-toxic. A small quantity (approximately one tablespoon) is unlikely to cause harm.

SECTION 5 – FIRE FIGHTING MEASURES

Flash Point (method): N/D (est. >200°F)

Extinguishing Media: Use water spray, foam, or carbon dioxide when fighting fires involving this material.

Protection of Firefighters: As in any fire, wear NIOSH approved self-contained breathing apparatus pressure-demand and full protective gear.

Fire and Explosion Hazards: Material will not burn.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Personal Precautions: Slippery: can cause slips and falls if walked on.

Clean Up Methods: Contain spill with sand or other diking material. Soak up small spills with absorbent material. Dispose of in accordance with federal, state, and local regulations.

(See also Section 8 for information on Exposure Controls and Personal Protective Equipment.)



MATERIAL SAFETY DATA SHEET

SECTION 7 – HANDLING AND STORAGE

Handling: Avoid prolonged or repeated contact with skin. Avoid contact with eyes. Wash hands before eating, drinking, or using the toilet.

Storage: **Keep from freezing.** Keep container closed when not in use.

SECTION 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: If necessary, use general room dilution ventilation, process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

Personal Protective Equipment (PPE):

Eye Protection: Eye contact should be avoided. Where eye contact is likely, wear chemical splash goggles and/or full-face shield.

Skin Protection: Wear gloves to prevent prolonged skin contact.

Respiratory Protection: None needed under normally anticipated use conditions. If vapor levels exceed allowable limits, wear a NIOSH approved air-purifying respirator with an organic vapor cartridge.

General Hygiene Practices: Avoid eye and skin contact. Avoid breathing vapors. Wash hands before eating, drinking, or using the toilet.



MATERIAL SAFETY DATA SHEET

SECTION 9 – PHYSICAL DATA

| | | | |
|-----------------------------|---|--------------------------------------|---------------|
| Appearance: | Clear flowable liquid | Odor: | Mild odor |
| Physical State: | Liquid | pH: | 7 to 10 |
| Boiling Point: | Above 200°F | Melting Point: | <32°F |
| Vapor Pressure: | N/D | Vapor Density: | N/D |
| Odor Threshold: | N/D | Viscosity: | 10 to 200 cps |
| Solubility in Water: | Dilutable in water | Specific Gravity (water = 1): | 1.0-1.2 |
| Material VOC: | Material, less water, contains less than 125 grams per liter Volatile Organic Compounds | | |

SECTION 10 – STABILITY AND REACTIVITY

| | | | |
|--|----------------------|-------------------------|------------|
| Stability: | Stable, non-reactive | Incompatibility: | None known |
| Hazardous Polymerization: | Will not occur | | |
| Hazardous Decomposition Products: | None known | | |

SECTION 11 – TOXICOLOGICAL INFORMATION

Carcinogenicity: This material is not considered a carcinogen by IARC or NTP and is not regulated as a carcinogen by OSHA.

(See also Section 15 for related information.)

SECTION 12 – ECOLOGICAL INFORMATION

Chemical Fate and Effects: No data available.



MATERIAL SAFETY DATA SHEET

SECTION 13 – DISPOSAL CONSIDERATIONS

Recommended Waste Disposal Method: This material is not considered hazardous waste under Federal Hazardous Waste Regulations (40CFR 261). However, state and local requirements for waste disposal may be more restrictive or otherwise differ from federal regulations. Chemical additions, processing, or otherwise altering this material may render the waste management information presented in this MSDS incomplete, inaccurate, or otherwise inappropriate. Consult all applicable federal, state, and local regulations regarding the proper disposal of this material.

SECTION 14 – TRANSPORTATION INFORMATION

Regulated by the DOT: Not regulated

DOT Proper Shipping Name: Paint

SECTION 15 – REGULATORY INFORMATION

CERCLA:

The Comprehensive Environmental Response Compensation and Liability Act of 1980 (CERCLA) requires notification to the National Response Center for releases of quantities of Hazardous Substances equal to or greater than the reportable quantities (RQs) in 40 CFR 302.4 (for CERCLA 102).

Components present in this product at a level which could require reporting under the statute are:

| <u>Chemical Name</u> | <u>CAS #</u> | <u>Maximum Concentration (Wt. %)</u> |
|---------------------------------|--------------|--------------------------------------|
| Diethylene glycol n-butyl ether | 000112-34-5 | 3% |
| Amorphous silica | 112926-00-8 | 2% |



MATERIAL SAFETY DATA SHEET

SARA Title III, section 311/312:

The Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III requires emergency planning based on Threshold Planning Quantities (TPQs) and release reporting based on Reportable Quantities (RQs) in 40 CFR 355 (used for SARA 302, 304, 311, and 312).

Components present in this product at a level which could require reporting under the statute are:

| <u>Chemical Name</u> | <u>CAS #</u> | <u>Maximum Concentration (Wt. %)</u> |
|---------------------------------|--------------|--------------------------------------|
| Diethylene glycol n-butyl ether | 000112-34-5 | 3% |
| Amorphous silica | 112926-00-8 | 2% |

SARA Title III, section 313:

The Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III requires submission of annual reports of release of toxic chemicals that appear in 40 CFR 372 (for SARA 313).

Components present in this product at a level which could require reporting under the statute are:

| <u>Chemical Name</u> | <u>CAS #</u> | <u>Maximum Concentration (Wt. %)</u> |
|---------------------------------|--------------|--------------------------------------|
| Diethylene glycol n-butyl ether | 000112-34-5 | 3% |
| Amorphous silica | 112926-00-8 | 2% |

TSCA:

The components of this mixture are listed in the Toxic Substance Control Act Inventory of Chemical Substances.

This product does not contain any chemicals that would require export notification under Section 12(b) of the TSCA regulation.



MATERIAL SAFETY DATA SHEET

SECTION 16 – OTHER INFORMATION

Legend: **N/A:** Not Applicable **N/D:** Not Determined
N/E: Not Established **N/R:** Not Required
STEL: Short Term Exposure Limit **C:** Ceiling Value
cps: Centipoise **mg/m³:** milligrams per cubic meter
PPM: Parts Per Million **PPB:** Parts Per Billion
PEL: Permissible Exposure Limit **TLV:** Time Weighted Average
mppcf: million particles per cubic foot of air
ACGIH: American Conference of Governmental Industrial Hygienists
CPSC: Consumer Product Safety Commission
DOT: US Department of Transportation
FHSA: Federal Hazardous Substance Act
OSHA: Occupational Safety and Health Administration (US Dept. of Labor)
RCRA: Resource Conservation and Recovery Act
SARA: Superfund Amendment and Reauthorization Act
TSCA: Toxic Substance Control Act

HMIS Key

4 = Severe Hazard
3 = Serious Hazard
2 = Moderate Hazard
1 = Slight Hazard
0 = Minimal Hazard

Prepared by: Modern Masters Regulatory Compliance Manager,
Technical Management Department
9380 San Fernando Road, Sun Valley, California 91605 (818) 683-0201

Disclaimer: Modern Masters, Inc. believes, to the best of its knowledge, information, and belief, the information contained herein to be accurate and reliable as of the date of this material safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials and make no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and data to comply with all applicable international, federal, state, and local laws and regulations.